



FCS-3402 Version: 1

! Power supply unit is to be ordered separately.

GEMINI Cámara de red IP domo fijas, 2-Megapixel, H.265, Vandalproof, 802.3af PoE, Exteriores

The LevelOne FCS-3402 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-3402 Should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Key Features

- Compresión de vídeo: H.264, H.265, MJPEG
- Carcasa con grado de protección IP67 contra meteorología adversa
- Ranura de tarjetas Micro SDHC/SDXC integrada para el almacenamiento local
- Admite visión remota desde iPhone/Android phone a través de Internet

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
 IEEE 802.3u 100-BASE-TX, Fast Ethernet
 IEEE 802.3af Power over Ethernet (PoE)
 IEEE 802.1X Network Access Control
 TCP(IPv6/v4), UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP,FTP,SAMBA UPnP, SNMP, Bonjour

Sensor de imagen:

2-Megapixel 1/2.8" Progressive Scan CMOS

Lente:

Board LENS 4mm @F2.0

Puerto:

1 x RJ-45 10/100 Mbps PoE port
 Power Connector DC JACK
 Audio:In/Out
 I/O terminal block (1 DI/1 DO)
 1 x MicroSDHC/ MicroSDXC card slot

Botón / Perilla:

Reset

**Indicador:**

Power

Filtro de corte IR:

Removable infrared-cut filter for day & night function

IR LED:

Up to 30 Meter, Wavelength @ 850 nm

Tiempo de obturación:

1/3 s to 1/100,000 s

Ángulo de vista:

FOV: 86°, vertical FOV: 46°, diagonal FOV: 102°

Pan/Tilt/Zoom:

Digital Zoom to very high detail available on Software

Compresión de video:

Main stream: H.265/H.264

Sub-stream: H.265/H.264/MJPEG

Resolución:

50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720)

60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)

Formato de video de salida:

MPEG4

Entrada de alimentación:

12 VDC ± 25%, 5.5 mm coaxial power plug

PoE (802.3af, class 3)

El consumo de energía:

12 VDC, 0.4 A, Max: 5 W

PoE: (802.3af, 37 V to 57 V), 0.2 A to 0.13 A, Max: 7 W

Velocidad de datos:

Video Bit Rate: 32 Kbps to 8 Mbps

Capacidad de almacenamiento:

MicroSDHC /MicroSDXC card slot for local storage

Digital Zoom:

8X

Temperatura de funcionamiento (° C):

-30 °C to +60 °C (-22 °F to +140 °F)

Humedad de funcionamiento:

Humidity 95% or less (non-condensing)

Instalación:

Working with accessory kit:

ceiling , Wall, Pendant, Junction Box, Corner, Vertical Pole, Rain-proof Cap

Features

General:

Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark

Características de PoE:

PoE (802.3af, class 3)

Características de seguridad:

Motion detection, video tampering alarm, illegal login

Características de gestión:

Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
BLC, 3D DNR, WDR :120 dB

Funciones de video:

Region of Interest:1 fixed region for main stream and sub-stream

Performance

Cantidad de clientes:

Up to 32 users, 3 levels: Administrator, Operator and User
Simultaneous Live View:Up to 6 channels

Velocidad de fotogramas (fps):

Main Stream:

50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720)

60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)

Sub-Stream:

50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)

60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Iluminación mínima:

Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR

Physical Specifications

Dimensiones (W x D x H mm):

Φ 111 × 82.4 mm (Φ 4.4" × 3.2")

Peso (gramos):

410 g (1.3 lb.)

Color:

White

Approval and Compliance

EMI/EMS:

CE/FCC

Prueba ambiental:

IP67, IK10

Others:

ONVIF (PROFILE S, PROFILE G), ISAPI

Manufactured in ISO-9001 and ISO-14001 certified factory,

RoHS

Others

Navegadores compatibles:

IIE7+, Chrome18-42, Firefox5.0+, Safari5.02+

Compatibilidad:

Windows 7/8/10

Order Information

FCS-3402



Package Contents

FCS-3402

Screw Kit

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Accesorios



CAS-7301

Soporte de montaje en pared



CAS-7302

Soporte de montaje en pared con caja de conexiones



CAS-7303

Soporte de montaje en poste, Clamping Range 2.6"-5"



CAS-7304

Soporte de montaje en techo inclinado



CAS-7306

Soporte de montaje colgante




CAS-7307

Soporte de montaje en esquina



CAS-7309

Pantalla protectora



CAS-7310

Junction box for Dome Camera

Digital Data Communications GmbH
Hohe Straße 1, 44139 Dortmund, Germany

Specifications are subject to change without notice. No liability or responsibility for any errors or omissions in the content.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.