

## RJ45 CAT.5e for PROFINET®



### Application Advantage


- IP20 protection
- Suitable for solid and stranded conductors
- Die-cast zinc housing
- Color coded to PROFINET® standards
- Conforms to IEC 60603-7-51

### Approvals



Part Number	Conductor Size		Cable Outer Diameter		Standard Pack Size
	stranded	solid	in	mm	
21700605	27 - 22 AWG (7 wire)	24 - 22 AWG	0.197 - 0.354	5.0 - 9.0	10

## RJ45 CAT.6 Hirose TM21



### Application Advantage

- Suitable for solid and stranded conductors
- Anti-kink protection
- Screened against EMI
- Bend protection & guide plate included

### Approvals



#### Complete the Installation



Part Number	Conductor Size	Max. Cable Outer Diameter		Standard Pack
		in	mm	
CE6324	26 - 24 AWG	0.26	6.6	50

## RJ45 CAT.6A, field wireable



### Application Advantage

- IP20 protection
- Suitable for solid and stranded conductors
- Die-cast zinc housing
- Supports 10 Gigabit Ethernet
- Color coded to TIA/EIA-568 standards
- Conforms to IEC 60603-7-51
- Suitable for PROFINET® applications

### Approvals



Part Number	Color Code	Conductor Size		Cable Outer Diameter		Standard Pack Size
		stranded	solid	in	mm	
21700600	T568A	27 - 22 AWG (7 wire)	24 - 22 AWG	0.197 - 0.354	5.0 - 9.0	10
21700601	T568B	27 - 22 AWG (7 wire)	24 - 22 AWG	0.197 - 0.354	5.0 - 9.0	10
21700615		27 - 24 AWG (7 wire)	26 - 24 AWG		9.0	10
21700616		27 - 24 AWG (7 wire)	26 - 24 AWG		9.0	10